

Triple Interface Thermal POS Printer

Model No. SBV-80B-USE



Printing Method	Thermal Line Printing
Printing Speed	250mm/s
Resolution	8mm/s, 576 dots/line
Character Set	ANK character, GB18030 (Chinese)
	Font A: 12x24 dots
	Font B: 9x17 dots
	Jan / traditional form: 24 x 24 dots
Barcode Type	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / COADABAR / ITF / CODE39 / CODE93 / CODE128
Interface	USB + WLAN + Serial
Power	DC 24V 2.5A
Cash Drawer Control	DC 12V-24V / 1A
Reliability (MCBF)	150km
Work Environment	Temperature: 0~45°C; Humidity: 10~80%
Storage Environment	Temperature: -10~60°C; Humidity: 10~90%
Paper Width	80mm
Paper Thickness	0.06mm ~ 0.08mm
Weight	1.3kg (N.W.) 2.8kg (G.W.)
Dimensions	195mm (l) x 148mm (w) x 145mm (h)
Drivers	Win 9X / Win ME / Win 2000 / Win 2003 / Win NT / Win XP / Win Vista / Windows 7 / Linux / OPOS
Auto-cutter	All cut or partly cut as optional
Printing command	Compatible with POS/ESC command set
Line Spacing	3.75mm (can be adjusted by command)